



TECHNICAL SHEET

FA 30 600 15

Designation :

Forked energy absorbing kernmantle rope lanyard

- Energy absorber in 44mm wide webbing which reduces the impact of the fall less than 6 KN
- 12mm diam polyamide kernmantle rope lanyard
- Loops protected by an abrasion resistant thimble
- Spliced end protected with strong covering sleeve

Connectors :

2 scaffold hooks opening 55 mm , ref. FA5020755 and 1 screw-locking karabiner opening 17 mm, ref. FA5010117.

Compliance :

EN355 : 2002 and tested as per VG11 - 89/686/CEE



Length :

Lg 1.5 mtr (Connectors included)

Materials :

Lanyards : polyamide

Absorber : polyester and polyamide

Connectors : steel

HS code

56090090

Carton size / Pieces

40x40x24 / 10

Unit weight

1.82 kg

AET : N° 4333 Issue 2 Extension 1

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11 : GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



maj : 08/12

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

